

Modelling of Work Efficiency in Cable Traction with Tractor Implementing the Least-Squares Methods and Robust Regression

Saliha Ünver-Okan

Abstract

Wood-harvesting activities are conducted by contractors through tendering based on prices determined by the amount of transported wood, land conditions and transport method parameters. Managers should determine the average completion time of the work and the base price accurately to prevent both work and contractor losses prior to the tender and note the same in the tender contract. Thus, prediction of productivity in wood production is of great importance in the determination of the work duration and cost. In this context, the aim of the present study was to determine the most accurate estimation model that would predict productivity (P) based on log volume (V_l), route slope (P) and winching distance (D) in uphill cable skidding activities with a drum tractor. In the current study, estimation models were developed that use both linear regression through SPSS employing all data and the robust regression method that minimizes the effect of outliers. Harvesting units were selected among pure spruce (*Picea orientalis* (L.) Link) stands via the uphill cable-skidding method with a tractor in the North-East of Turkey. Route slope, winching distance, log volume and time-consumption data were collected in the chosen harvesting units and productivity prediction models were developed with these data. In this study, the productivity estimation was performed using linear regression in SPSS and robust regression methods prepared in MATLAB environment. The coefficients calculated by these methods were statistically tested, and it was determined that the winching distance coefficient was insignificant with both methods. Thus, the productivity estimation model was re-determined with both methods based on the slope and log volume parameters, and the findings were compared. Additionally, the standard errors of the coefficients of both models were compared and it was concluded that the robust method was more sensitive than the SPSS regression method.

Keywords: prediction model, productivity, time measurement, cable logging, uphill skidding

1. Introduction

Forestry includes different activities, such as establishment of the stand, silviculture and maintenance activities, production of wood material or secondary products, marketing and sales, planning and construction of forest buildings, control of forest fires and pests (i.e., insects, fungi) and recreational activities. One of the most important forestry activities is wood production, which is the main source of income for forest enterprises and requires periodic interventions in the forest.

Wood production consists of three main stages: cutting/felling, extraction/primary transport and transportation/secondary transport. The process of extraction is technically difficult, ergonomically risky and expensive and includes heavy work that could lead to significant environmental damage (Ünver-Okan 2017). During log extraction, various machinery such as forwarders, skidders, tractors, harrowers, helicopters, balloons and tower yarders, are used (Ibrahimovic 2016). However, expensive machines

may not be used in countries with less favourable economic conditions (Blakeney 1992, Wang et al. 2005). In Turkey, where approximately half of the forests are dispersed in areas with a slope higher than 40%, the cable-skidding method with drummed forestry tractors is predominantly used uphill, while tower yarders are used occasionally (Acar et al. 2015).

When using the method of cable-skidding with a forestry tractor, the cable on the drum of the forestry tractor, which is fixed roadside, is pulled to the location of the logs by a worker, tied to a log, and the tractor engine pulls the cable to extract the log to the roadside. The utility of the cable-skidding method depends on the presence of a forest road; the maximum winching distance of tractors is between 100 and 120 m (Erdaş et al. 2014).

Certain studies report that the main limiting factors surrounding the decision to select the extraction method with a harvesting unit as well as the productivity of the machine are the silviculture, forest operation management, terrain condition, winching distance, tree size and route slope (Akay et al. 2004, Ghaffariyan et al. 2012, Spinelli et al. 2010). These parameters have a negative effect on productivity, especially in uphill extraction operations. Kováčsová and Antalová (2010) emphasized that forests should be operated with optimum productivity to meet the requirements of both present and future generations.

Wood-production activities are required to be completed within a certain period of time owing to the fact that they are conducted in natural conditions and with living material. As per the forestry regulations in Turkey, wood-logging operations are tendered to contractors with the stumpage sale method or forest villagers based on the unit price. In both cases, the operators should make an accurate work plan, determining the completion time of the work and the open tender price that should be specified accurately. Thus, it is of great importance to anticipate work productivity and come up with an adequate plan in wood production. One of the most commonly used methods is working time studies to analyse productivity of harvesting systems (Gallis 2004, Gallis and Spyroglou 2012, Savelli et al. 2010).

Regression analysis is one of the most commonly used statistical methods of estimation models to establish the correlation between two or more variables (Khamis and Razak 2017). As calculation with the LSM is rather easy, it is the preferred method for most regression applications (Wu and Yu 2018). However, it was demonstrated in various works that outlier or multi-polar/missing data within a data set may adversely affect regression results (Hekimoğlu and Berber 2003, Wen et al. 2013). In such cases, it is more

adequate to use the robust method, which could provide more reliable results by limiting the weight of outliers (Al-Amleh 2015). With the robust regression method, the measurements are affected neither by the errors in these measurements nor the errors in others, hence the negative impact of measurement errors on the results are reduced. This method permits more accurate determination of rough erroneous measurements without dispersing the effect of outliers. Therefore, a model, where matching data produces reliable results, could be designed.

The objective of the study was to design a model to accurately estimate effective productivity (P_e), where log volume (V_t), route slope (P) and winching distance (D) were known in a harvesting unit, where uphill tractor cable skidding was carried out. For this purpose, the effective productivity estimation for cable skidding was modelled with two methods: 1) Statistical Package for the Social Sciences (SPSS) linear regression; and 2) robust regression, with a final comparison of both methods.

2. Material and Methods

The study was performed in the East Black Sea forests in North-East of Turkey during 2016–2017. Route slope, winching distance, log volume and winching time data were collected from harvesting units that utilize uphill cable winching with a forest tractor. All harvesting units were pure spruce (*Picea orientalis* (L.) Link) stands of a middle age class and these forests had a closure of 0.71 to 1.00. The slopes of the skidding routes between 40–80% were measured with an inclinometer and winching distances between 38 and 115 m were evaluated with a steel tape measure.

In the study, 247 logs were extracted uphill using a MB-Track 900 model forest tractor. One log was skidded each time. Diameters (d) in cm and lengths (L) in m of the logs were measured. The volume of the transported logs (V_t) in m^3 was calculated with Huber's formula (Castellanos et al. 2007, The Forest Service 1999):

$$V_t = \frac{\pi \times d^2}{4000} L \quad (1)$$

Time measurements were performed with a stopwatch and the winching times (t) in h for each log were determined by the reset time measurement technique. Effective productivity of the system (P_e) in m^3/h was calculated as (Mederski 2006):

$$P_e = \frac{V_t}{t} \quad (2)$$

The regression equation for effective productivity (P_e) included skidded log volume (V_i), route slope (P) and winching distance (D):

$$P_{e_i} = b_0 + b_1 V_{t_i} + b_2 P_i + b_t D_i \quad (3)$$

Where:

b_0, b_1, \dots, b_t coefficients

i number of data ($i=1, 2, \dots, 120$).

The equation was solved with the SPSS linear regression and robust regression methods. Significant coefficients were determined for each solution and regression equations were written with these coefficients.

2.1 Regression Analysis

The regression is a popular method that determines the correlation between one independent variable and one or more dependent variables with a mathematical function (Uyanık and Güler 2013). In the literature, there are statistical estimation methods such as, the least squares method (LSM) (Koch 1999), weighted least squares (Draper and Smith 1998), robust regression (Chen and Pinar 1998, Gross 2003, Rousseeuw and Leroy 1987, Staudte and Sheater 1990), genetic algorithm (Pan et al. 1995) and artificial neural networks (Stern 1996).

The relationship between the inputs and outputs in a multivariate linear regression model was expressed as:

$$y = b_0 + b_1 x_1 + b_2 x_2 + \dots + b_t x_t + \varepsilon \quad (4)$$

Where:

y dependent variable

x_1, x_2, \dots, x_t independent variables

ε random error

t number of unknown parameters.

2.1.1 The Least-Squares Method (LSM)

In the estimation of model parameters, the LSM was applied, and the objective function was written as:

$$\sum_{i=1}^n \left[y_i - (b_0 + b_1 x_1 + b_2 x_2 + \dots + b_t x_t) \right]^2 \rightarrow \min. \quad (5)$$

As (ε) was the opposite of correction (v), when error was replaced by correction in Eq. 4, the following equation was obtained:

$$v_i = b_0 + b_1 x_1 + b_2 x_2 + \dots + b_t x_t - y_i \quad (6)$$

This equation could be written as a matrix:

$$V = Ab - y$$

$$\begin{bmatrix} v_1 \\ v_2 \\ \vdots \\ v_n \end{bmatrix} = \begin{bmatrix} 1 & x_1 & x_2 & \dots & x_t \\ 1 & x_1 & x_2 & \dots & x_t \\ \vdots & \vdots & \vdots & \vdots & \vdots \\ 1 & x_1 & x_2 & \dots & x_t \end{bmatrix} \begin{bmatrix} b_0 \\ b_1 \\ b_2 \\ \vdots \\ b_t \end{bmatrix} - \begin{bmatrix} y_1 \\ y_2 \\ \vdots \\ y_n \end{bmatrix} \quad (6)$$

Where:

y output vector

A coefficient matrix

b regression coefficient matrix

V correction vector.

The regression coefficients were obtained with the LSM method as:

$$b = (A^T P A)^{-1} A^T P y \quad (8)$$

Where:

P weight matrix of input variables

The reverse weight matrix of the coefficients (Q_{bb}) was obtained with Eq. 8 as:

$$Q_{bb} = (A^T P A)^{-1} \quad (9)$$

The average error (m_o) of the unit measure was determined with the correction vector (V) calculated by the coefficients vector (b) put in Eq. 7 as:

$$m_o = \pm \sqrt{\frac{V^T P V}{n - u}} \quad (10)$$

Where:

n number of measurements

u number of unknowns.

The standard error (SE) for regression parameters (m_b) was calculated as:

$$m_{bi} = \pm m_o \sqrt{q_{b_i b_i}} \quad (11)$$

Where:

$q_{b_i b_i}$ i-diagonal of Q_{bb} matrix

The reverse weight matrix of the corrections (Q_{vv}) was calculated as:

$$Q_{vv} = P^{-1} - A Q_{bb} A^T \quad (12)$$

The standard error of corrections was calculated as:

$$Q_{vv} = P^{-1} - A Q_{bb} A^T \quad (13)$$

The significance of the regression coefficients obtained with Eq. 8 was tested as:

$$T_{bi} = \frac{|b_i|}{m_{b_i}} = \frac{|b_i|}{m_0 \sqrt{q_{b_i b_i}}} \geq t_{f, 1-\frac{\alpha}{2}} \quad (14)$$

Where:

- $q_{b_i b_i}$ i-diagonal element in reverse weight matrix of corrections (Q_{bb})
- $t_{f, 1-\frac{\alpha}{2}}$ table value for t distribution in degrees of freedom, f (Koch 1999)

2.1.2 Robust Regression Method

Although normal distribution of errors is assumed in LSM, in most applications, the normal distribution of errors cannot be ensured. An incorrect measurement adversely affects the LSM estimator and estimation value. Outliers impair all LSM findings, and thus all test sizes owing to the spillover effect. These cause the regression curve obtained with LSM to shift towards the outliers. Therefore, outliers are a serious problem in LSM analysis. One of the methods to overcome this problem is the robust regression method (Gallegos and Ritter 2005, Maronna and Zamar 2002, Meer et al. 1991, Wilcox 1997).

The robust regression method categorizes the measurements into reliable data and outliers. Reliable data have random errors, while the outliers have gross errors. The robust regression method is different from the LSM method in that it is not affected by outliers. Specifically, the parameters are calculated by assigning iteratively smaller weights to the outliers (Caspary and Borutta 1987, Gao et al. 1992, Hampel et al. 1986, Yang 1994, Yang et al. 2002).

The objective function (ρ) was written in the robust estimation method as:

$$\sum_{i=1}^n \rho(v_i) \rightarrow \min. \quad (15)$$

The derivative of the objective function was taken to obtain the prediction function (ψ) as:

$$\rho\psi(v_i) = \frac{\partial \rho}{\partial v_i} = \rho'(v_i) \quad (16)$$

and weight function (W) as:

$$W(v_i) = \frac{\psi(v_i)}{v_i} = W_i \quad (17)$$

The prediction was made iteratively by re-weighting the LSM method. In each iteration, standardized corrections were compared with a limit value and new weights of the data were determined based on the selected weight function. The iteration was maintained

until the desired convergence and the new weights of outliers were gradually reduced (Hekimoğlu and Berber 2003).

The iterated weight matrix was determined as:

$$P_i = P W_{i-1} \quad (18)$$

Where:

- i number of iteration

The robust weight matrix in the initial iteration accepted as the unit matrix ($W_0=I$).

The parameters were calculated with the LSM based on Eqs. (7) and (8) as:

$$b_i = (A^T \bar{P}_i A)^{-1} A^T \bar{P}_i y \quad (19)$$

Iteration was maintained until the difference between the b_{i+1} and b_i parameters were insignificant. It was observed that the weights of the outliers were diminished after each iteration, and some were even observed to approach zero. The significance tests of the regression coefficients were conducted with Eq. 14. Then, the regression equation was obtained with the significant coefficients.

Various weight functions are used in robust regression analysis (Gökulp et al. 2008) (Table 1).

Table 1 Commonly used robust weight functions

Estimation Method	Weight Functions
Andrews M-Estimation	$W_i = \begin{cases} \frac{\sin\left(\frac{v_i}{c}\right)}{\left(\frac{v_i}{c}\right)} & v_i \leq c\pi \\ 0 & v_i > c\pi \end{cases}$
Huber M-Estimation	$W_i = \begin{cases} 1 & v_i \leq c \\ \frac{c}{ v_i } & v_i > c \end{cases}$
Beaton-Tukey M-Estimation	$W_i = \begin{cases} \left[1 - \left(\frac{v_i}{c}\right)^2\right]^2 & v_i \leq c \\ 0 & v_i > c \end{cases}$
Danimarck Method	$W_i = \begin{cases} \exp\left(-\frac{v_i^2}{c^2}\right) & v_i > c \\ 1 & v_i \leq c \end{cases}$

The limit value parameter (c) for the weight functions in Table 1 can be determined with various techniques. In order for robust methods to provide accurate and reliable results, the limit value parameters should be determined as accurately as possible. The limit value was based on the assumption that observational errors would be scattered within the limits of $\pm c$ within a certain probability. The limit value could be assumed as:

$$c = ks_0 \quad (20)$$

Where:

s_0 preliminary standard error for the measurement set

Instead of $|v_i| \leq c$, standardized values of the corrections ($\frac{v_i}{m_{v_i}} \leq k$) could be taken. The H_0 hypotheses could be constructed as:

$$H_0 : E(v) = 0 \quad (21)$$

and test size (T_i) could be tested as:

$$T_i = \frac{|v_i|}{m_{v_i}} = \frac{|v_i|}{m_0 \sqrt{q_{v_i v_i}}} \leq t_{f, 1 - \frac{\alpha}{2}} \quad (22)$$

Where:

$q_{v_i v_i}$ i^{th} diagonal element in the weight matrix of corrections (Q_{vv})

$t_{f, 1 - \frac{\alpha}{2}}$ t -table value in degrees of freedom f

Using Eq. 22, the limit value was calculated for each correction as:

$$c_i = m_0 \sqrt{q_{v_i v_i}} t_{f, 1 - \frac{\alpha}{2}} \quad (23)$$

When the weights of the data were different, the limit value after the first iteration in Eq. 23 was:

$$c_i = m_0 \sqrt{q_{v_i v_i}} \sqrt{\bar{P}_i} t_{f, 1 - \frac{\alpha}{2}} \quad (24)$$

A common limit value was calculated by taking the average of c values calculated as (Gökalp and Boz 2005):

$$c = \frac{\sum_{i=1}^n c_i}{n} \quad (25)$$

Based on empirical studies, statisticians suggest that the limit value c could be taken as 1.5 or 2 (Somoogyi 1988). However, calculating the limit value c separately for each measure with Eq. 25 provides a more realistic decision.

3. Results and Discussion

3.1 SPSS Regression

The correlation of several parameters of the harvesting operations with productivity is generally determined by regression models (Gallis 2004). The linear regression function was established according to Eq. 3 using the log volume, slope and transport distance for effective productivity in the uphill tractor cable-skidding method. The coefficients of the parameters and the significance levels of these coefficients were determined by SPSS from Eq. 3 (Table 2).

Table 2 The coefficients of slope, volume, distance and significance testing with SPSS

Model	Unstandardized Coefficients		Standardized coefficients	t	Sig.
	B	SE	Beta		
(Constant)	4.397	.779		5.642	.000
Slope	-2.357	.816	-.137	-2.887	.004
Distance	-.004	.006	-.028	-.585	.559
Volume	5.383	.403	.655	13.368	.000

It was found that the distance coefficient was not significant at $p > 0.05$ (Table 2). Therefore, the regression equation for effective productivity was reconstructed with log volume and slope as:

$$P_{e_i} = b_0 + b_1 V_{t_i} + b_2 P_i \quad (26)$$

The coefficients of the parameters and the significance levels of these coefficients were re-calculated by SPSS from Eq. 26 (Table 3).

Table 3 The coefficients of slope, volume and significance testing with SPSS

Model	Unstandardized coefficients		Standardized coefficients	t	Sig.
	B	SE	Beta		
(Constant)	4.188	.692		6.054	.000
Slope	-2.392	.813	-.140	-2.943	.004
Volume	5.325	.390	.648	13.662	.000

Thus, the regression equation of effective productivity for uphill forestry tractor cable-skidding tech-

nique was determined using significant coefficients with linear regression in SPSS as:

$$P_{e_i} = 4.188 + 5.325 V_{t_i} - 2.392 P_i$$

$$(R^2 = 0.481, F = 113.065, p < 0.05) \quad (27)$$

Previous studies showed that productivity was generally affected by volume (Proto et al. 2018), distance (Nikooy et al. 2013), slope (Gilanipoor et al. 2012), the number of logs in each cycle (Gholami and Majnounian 2008) and interaction between them (Mousavi 2009, Naghdi 2004, Pilevar 1996). While it was found that distance affected productivity in some studies (Nikooy 2007, Wang 2004), it was determined that distance had no effect on productivity by Mousavi and Nikooy (2014) similar to this study. On the other hand, Gilanipoor et al. (2012) determined that productivity depended on slope and volume similar to the findings in this study.

3.2 Robust Regression

The regression coefficients in Eq. 3 were calculated by the robust regression method with iterations. These calculations were performed with the software written by the author in the MATLAB environment. The Huber M-Estimation was used as the estimation method (Table 1). In the Huber M-Estimation, the limit value (c) was determined by Eq. 25. Robust weights (W) were calculated from Eq. 17. The iterated weight matrix (P_i) was determined by Eq. 18. Regression equation coefficients in Eq. 3 were calculated by Eq. 19 after iterations. With this method, the significance of the coefficients was tested by comparing the test size (T_{bi}) and t -table value (Table 4).

Table 4 The coefficients of slope, volume, distance and significance testing with the robust regression method

Coefficients b_i	Test Size T_{bi}	t-Table Value $t_{f,1-\frac{\alpha}{2}}$	Decision $T_b \geq t_{f,1-\frac{\alpha}{2}}$
$b_0 = 3.0228$	5.459	1.969	Significant
$b_1 = 5.5073$	18.899	1.969	Significant
$b_2 = -1.4064$	2.464	1.969	Significant
$b_3 = -0.0011$	0.253	1.969	Insignificant

It was found that the winching distance coefficient (b_3) in Eq. 3 was insignificant (Table 4). Therefore, the effective productivity regression coefficients were cal-

culated with log volume and route slope, which were determined as significant, and standard errors for the coefficients (m_{bi}) were calculated with Eq. 11 with significance tests conducted (Table 5).

Table 5 The coefficients of slope, volume and significance testing with the robust regression method

Coefficients b_i	SE m_{bi}	Test Size T_{bi}	t-Table Value $t_{f,1-\frac{\alpha}{2}}$	Decision $T_b \geq t_{f,1-\frac{\alpha}{2}}$
$b_0 = 3.0940$	0.495	6.253	1.969	Significant
$b_1 = 5.5182$	0.284	19.416	1.969	Significant
$b_2 = -1.3886$	0.570	2.436	1.969	Significant

It was found that the transport distance coefficient was not significant (Table 5). For this reason, log volume and slope coefficients were re-calculated from the robust regression method in Eq. 26 and significance tests were performed. Hence, the regression equation of effective productivity for the uphill forestry tractor cable-skidding technique was determined using significant coefficients with the robust regression method as follows:

$$P_{e_i} = 3.0940 + 5.5182 V_{t_i} - 1.3886 P_i \quad (28)$$

In the literature, various studies comparing LSM and robust regression methods have been made. Muhlbauer et al. (2009) found that external observations might bias the LSM trend estimate and lead to an overly high or low estimate. Therefore, it was determined that the robust method was more suitable than LSM for estimation modelling. Similar to this study, Hekimoğlu and Erenoğlu (2005) determined that it was more appropriate to use robust methods in cases of outliers.

4. Conclusions

This work is of great importance and represents the most accurate estimation of the productivity of production and realization of production during wood-extraction activities, one of the most difficult and expensive stages of wood production. In the literature, productivity prediction models were largely developed by linear regression analysis in SPSS software. However, for the linear regression model of the SPSS program, sufficiently accurate results may not be obtained because the coefficients are calculated accord-

ing to the LSM method from all data containing outliers. Therefore, this research sought to investigate more sensitive determination of productivity estimation. For this purpose, productivity estimation was carried out by the robust estimation method, which minimizes the effects of outliers, and the results were compared with SPSS estimation.

In this study, spruce logs with the volume of 0.28–2.35 m³ were transported uphill with a forest tractor at 38–115 m distances in harvesting units having a slope between 40 and 80%. The productivity estimations were produced using SPSS and the Huber-M estimation with the robust regression method prepared in MATLAB by taking the slope, volume and transport distance. With both estimation methods, it was determined that slope and volume had a significant effect on productivity, while the winching distance was not effective. It was determined that the productivity was directly proportional to volume and inversely proportional to slope. The standard errors of the coefficients of both models were compared and it was concluded that the robust method was more sensitive than the SPSS regression method.

In future studies, productivity estimations for cable traction with forestry tractors should be investigated for different slopes, volumes and tree species. In addition, it is recommended that productivity estimates for different extraction methods be made with different robust estimation methods.

Acknowledgements

This study was financially supported by the »Scientific and Technological Research Council of Turkey (TUBITAK)« (The project number: 115O017).

5. References

- Acar, H.H., Kaya, A., Ünver-Okan, S., Üçüncü, K., 2015: Evaluation of skidding system by MB-Track 900 forest tractors on steep slope in thinning operations. *International symposium FORMEC*, 4–8 October, Linz, Austria, 1–6 p.
- Akay, A.E., Erdas, O., Session, J., 2004: Determining productivity of mechanized harvesting machines. *Journal of Applied Sciences* 4(1): 100–105. <https://doi.org/10.3923/jas.2004.100.105>
- Al-Amleh, M.A.A.H., 2015: Robust methods in regression analysis: Comparison and improvement. Master's Thesis, Zarqa University, Jordan, 68 p.
- Blakeney, K.J., 1992: Environmentally friendly helicopter logging in Papua New Guinea. *Symposium on Harvesting and Silviculture for Sustainable Forestry in the Tropics*. Forest Research Institute Malaysia, October 5–9, 145–150.
- Caspary, W., Borutto, H., 1987: Robust estimation in deformation models. *Survey Review* 29(223): 29–45. <https://doi.org/10.1179/sre.1987.29.223.29>
- Castellanos, A., Blanco, A.M., Palencia, V., 2007: Applications of radial basis neural networks for area forest. *International Journal Information Theories & Applications* 14(3): 218–222.
- Chen, B., Pinar, M.Ç., 1998: On Newton's method for Huber's robust M-estimation problems in linear regression. *Swets & Zeitlinger* 38(4): 674–684. <https://doi.org/10.1007/BF02510408>
- Draper, N.R., Smith, H., 1998: *Applied Regression Analysis*, Wiley. 736 p.
- Erdas, O., Acar, H.H., Eker, M., 2014: Transport techniques for forest products. *KTU Faculty of Forestry, Trabzon, Publish No: 233/39*, 504 p.
- Gallegos, M.T., Ritter, G., 2005: A Robust method for cluster analysis. *The Annals of Statistics* 33(1): 347–380. <https://doi.org/10.1214/009053604000000940>
- Gallis, C., 2004: Comparative cost estimation for forwarding small-sized beech wood with horses and mini-skidder in northern Greece. *Forest Products Journal* 54(11): 84–90.
- Gallis, C., Spyroglou, G., 2012: Productivity linear regression models of tree-length harvesting system in natural coastal Aleppo Pine (*Pinus halepensis* L.) forests in the Chalkidiki area of Greece. *Croatian Journal of Forest Engineering* 33(1): 115–123.
- Gao, Y., Krakinwsky, E.J., Czompo, J., 1992: Robust testing procedure for detection of multiple blunders. *Journal for Survey Engineering ASCE* 118(1): 11–23. [https://doi.org/10.1061/\(ASCE\)0733-9453\(1992\)118:1\(11\)](https://doi.org/10.1061/(ASCE)0733-9453(1992)118:1(11))
- Ghaffariyan, M.R., Sessions, J., Brown, M., 2012: Machine productivity and residual harvesting residues associated with a cut-to-length harvest system in southern Tasmania. *Southern Forests: Journal of Forest Science* 74(4): 229–235. <https://doi.org/10.2989/20702620.2012.741770>
- Gholami, M.J., Majnounian, B., 2008: Productivity and cost of wheeled skidder in Hyrcanian forest. *International Journal of Natural and Engineering Sciences* 2(3): 99–103.
- Gilanipoor, N., Najafi, A., Heshmat Alvaezin, S.M., 2012: Productivity and cost of farm tractor skidding. *Journal of Forest Science* 58(1): 21–26. <https://doi.org/10.17221/4804-JFS>
- Gökalp, E., Güngör, O., Boz, Y., 2008: Evaluation of different outlier detection methods for GPS networks. *Sensors* 8(11): 7344–7358. <https://doi.org/10.3390/s8117344>
- Gökalp, E., Boz, Y., 2005: Comparison of robust M-estimations in determination of the outlying baseline vectors in GPS networks. *Map Journal* 134: 1–17.
- Gross, J., 2003: *Linear Regression*. Springer Verlag, Berlin, Heidelberg, New York, 398 p.
- Hampel, F., Ronchetti, E., Rousseeuw, P., Stahel, W., 1986: *Robust statistics: The approach based on influence functions*. John Wiley and Sons Inc., New York, 536 p.

- Hekimoğlu Ş., Berber, M., 2003: Effectiveness of robust methods in heterogeneous linear models. *Journal of Geodesy* 76(11–12): 706–713. <https://doi.org/10.1007/s00190-002-0289-y>
- Hekimoğlu, Ş., Erenoğlu, R.C., 2005: Outlier detection by using robust methods and comparison results to tests for outliers for leveling networks. 2nd Engineering Survey Symposium, 23–25 October, Istanbul, Turkey, 481–490.
- Ibrahimovic, A.Q., 2016: Suspended forestry machines for sustainable forestry. Ph.D Thesis, KTH Royal Institute of Technology, Stockholm, Sweden.
- Khamis, A., Razak, N.A.A., 2017: A comparative study of robust regression methods in modeling the currency in circulation in Malaysia. *International Journal of Science and Research* 6(4): 241–244.
- Kováčsová, P., Antalová, M., 2010: Precision forestry-definition and technologies. *Šumarski list* 134(11–12): 603–611.
- Koch, K.R., 1999: Parameter estimation and hypothesis testing in linear models. Springer, Berlin, Heidelberg, New York, 334 p.
- Maronna, R.A., Zamar, R.H., 2002: Robust estimates of location and dispersion for high-dimensional data sets. *Technometrics* 44: 307–317. <https://doi.org/10.1198/004017002188618509>
- Mederski, P.S., 2006: A comparison of harvesting productivity and costs in thinning operations with and without mid-field. *Forest Ecology and Management* 224: 286–296. <https://doi.org/10.1016/j.foreco.2005.12.042>
- Meer, P., Mintz, D., Rosenfeld, A., Kim, D.Y., 1991: Robust regression methods in computer vision: A review. *International Journal of Computer Vision* 6(1): 59–70. <https://doi.org/10.1007/BF00127126>
- Mousavi, R., 2009: Comparison of productivity, cost and environmental impacts of two harvesting methods in northern Iran: Short-log vs. long-log. *Dissertationes Forestales* 82: 93 p.
- Muhlbauer, A., Spichtinger, P., Lohmann, U., 2019: Application and comparison of robust linear regression methods for trend estimation. *Journal of Applied Meteorology and Climatology* 48(9): 1961–1970. <https://doi.org/10.1175/2009JAMC1851.1>
- Naghdi, R., 2004: Investigation and comparison of full tree and log utilization methods in order to presentation the best model forest roads network in Neka region (North of Iran). Ph.D. Thesis, Tarbiat Modarres University, Tehran, 238 p.
- Nikooy, M., Esmailnezhad, A., Naghdi R., 2013: Productivity and cost analysis of skidding with Timberjack 450C in forest plantations in Shafaroud Watershed, Iran. *Journal of Forest Science* 59(7): 261–266. <https://doi.org/10.17221/19/2013-JFS>
- Nikooy, M., 2007: Production optimization and reduction impact on forest by preparing harvest planning in Nav, Iran. Ph.D. Thesis, Tehran University, Tehran, 165 p.
- Pan, Z., Chen, Y., Kang, L., Zhang, Y., 1995: Parameter estimation by genetic algorithms for nonlinear regression, optimization techniques and applications. *Proceeding of ICO-PA'95* 2(1): 946–953.
- Pilevar, B., 1996: Calculation of cost in two harvesting system: Cable crane and ground skidding. Master Thesis, Tehran University, Tehran, 98 p.
- Proto, A.R., Macrì, G., Visser, R., Russo, D., Zimbalatti, G., 2018: Comparison of timber extraction productivity between winch and grapple skidding: A case study in southern Italian forests. *Forests* 9(2): 61–72. <https://doi.org/10.3390/f9020061>
- Rousseeuw, P.J., Leroy, A.M., 1987: Robust regression and outlier detection. John Wiley, New York, 329 p.
- Savelli, S., Cavalli, R., Baldini, S., Picchio, R., 2010: Small scale mechanization of thinning in artificial coniferous plantation. *Croatian Journal of Forest Engineering* 31(1): 11–21.
- Somogyi, J., 1988: Robust estimation and their use in geodesy. *Acta Geod. Geogh. Mont. Hung.* 23(1): 45–55.
- Spinelli, R., Magagnotti, N., Lombardini, C., 2010: Performance, capability and costs of small-scale cable yarding technology. *Small Scale Forestry* 9(1): 123–135. <https://doi.org/10.1007/s11842-009-9106-2>
- Staudte, R.G., Sheater, S.J., 1990: Robust estimation and testing. Wiley, New York, 376 p.
- Stern, H.S., 1996: Neural networks in applied statistics. *Technometrics* 38(3): 205–214.
- The Forest Service, 1999: Timber measurement manual: Standard procedures for the measurement of round timber for sale purposes in Ireland. The Forest Service of the Department of the Marine & Natural Resources, Ireland, 82 p.
- Ünver-Okan, S., 2017: Comparison of drummed forest tractor and portable winch systems for uphill extraction economical and technical aspects. TUBITAK Project Code: 115O017.
- Uyanık, G.K., Guler, N., 2013: A study on multiple linear regression analysis. *Procedia – Social and Behavioral Sciences* 106: 234–240. <https://doi.org/10.1016/j.sbspro.2013.12.027>
- Wang, J., Grushecky, S.T., McNeel, J. 2005: Production analysis of helicopter logging in west Virginia: A preliminary case study. *Forest Products Journal* 55(12): 71–76.
- Wang, J., Long, C., McNeel, J., Baumgras, J., 2004: Productivity and cost of manual felling and cable skidding in central Appalachian hardwood forests. *Forest Product Journal* 54: 45–51.
- Wen, Y.W., Tsai, Y.W., Wu, D.B.C., Chen, P.F., 2013: The Impact of Outliers on net-benefit regression model in cost-effectiveness analysis. *PLoS ONE* 8(6): 1–9. <https://doi.org/10.1371/journal.pone.0065930>
- Wilcox, R.R., 1997: Introduction to robust estimation and hypothesis testing. Academic Press, New York, 608 p.
- Wu, C., Yu, J.Z., 2018: Evaluation of linear regression techniques for atmospheric applications: the importance of ap-

appropriate weighting. *Atmospheric Measurement Techniques* 11: 1233–1250. <https://doi.org/10.5194/amt-11-1233-2018>

Yang, Y., 1994: Robust estimation for dependent observations. *Manuscript Geod* 19(1): 10–17.

Yang, Y., Song, L., Xu, T., 2002: Robust estimator for correlated observations based on bifactor equivalent weights. *Journal of Geodesy* 76 (6): 353–358. <https://doi.org/10.1007/s00190-002-0256-7>

Authors' addresses:

Asst. prof. Saliha Ünver-Okan, PhD *
e-mail: cansu@ktu.edu.tr
Karadeniz Technical University
Faculty of Forestry
Department of Forest Engineering
61080 Trabzon
TURKEY

* Corresponding author

Received: May 20, 2019

Accepted: October 23, 2019